

# PLAYER ONE SPORTS LIGHT



P1RGB



P1S/P1M



P1L/P1XL



PROJECT: \_\_\_\_\_

DATE: \_\_\_\_\_

TYPE: \_\_\_\_\_

PREPARED BY: \_\_\_\_\_



\*\* No DLC for RGB Models

## KEY FEATURES

- Sports lights available in following models:  
P1SRGB: 480W  
P1S: 500W  
P1M: 600W  
P1L: 850W  
P1XL: 1200W
- CCT: 5700K except 480W. 480W models tunable RGB.
- Standard yoke mount. Slipfitter mount, square beam mount, and rail mounting kits sold separately.
- Available NEMA beam spread of 2HX2V, 3HX3V & 4HX4V
- Suitable for wet locations
- 120-277V & 200-480V dimming driver. P1XL only available in 200-480V.
- Lightcloud Controller optional
- 10-year limited warranty

PLAYER ONE sports light with RGB option



RGB



100,000 HRS



WET RATED



IP RATING



120-277; 480V



LIGHTCLOUD ENABLED



LIGHTCLOUD BLUE ENABLED

## PERFORMANCE

MODEL#	P1RGB				P1RGB/480			
	RGB	RED	GREEN	BLUE	RGB	RED	GREEN	BLUE
WATTAGE	480W				480W			
INPUT WATTS	486.2W	299.4W	103.7W	84.2W	462.8W	218.8W	105.1W	88W
LUMENS	14,364	6,620	7,003	2,069	14,411	8,346	6,946	2,119
EFFICACY	29.5	22.1	67.5	24.6	31.1	38.1	66.1	24.1
CRI	-20	24	-16	-37	-24	23	-17	-38
VOLTAGE RATINGS	120-277V				200-480V			

MODEL#	P1S			P1S W/GLARE CONTROL SHIELD		
	2HX2V	3HX3V	4HX4V	2HX2V	3HX3V	4HX4V
COLOR TEMP	5700K			5700K		
NEMA BEAM SPREAD	2HX2V	3HX3V	4HX4V	2HX2V	3HX3V	4HX4V
WATTAGE	500W			500W		
INPUT WATTS	506.6W	500W	500.1W	506.3	499.7	499.9
LUMENS	72,476	67,221	66,951	58,753	47,688	51,262
EFFICACY	143.1	134.4	133.9	116.0	95.4	102.5
CRI	74	76	76	74	76	76
VOLTAGE RATINGS	120-277V			120-277V		

# PLAYER ONE SPORTS LIGHT



## PERFORMANCE

MODEL#	P1S/480			P1S/480 W/GLARE CONTROL SHIELD		
COLOR TEMP	5700K			5700K		
NEMA BEAM SPREAD	2HX2V	3HX3V	4HX4V	2HX2V	3HX3V	4HX4V
WATTAGE	500W			500W		
INPUT WATTS	506.1W	505.3W	505.3W	506	505	505.3
LUMENS	73,229	68,678	68,236	59,669	48,925	52,331
EFFICACY	144.7	135.9	135	117.9	96.9	103.6
CRI	74	76	76	75	76	76
VOLTAGE RATINGS	200-480V			200-480V		

MODEL#	P1M			P1M W/GLARE CONTROL SHIELD		
COLOR TEMP	5700K			5700K		
NEMA BEAM SPREAD	2HX2V	3HX3V	4HX4V	2HX2V	3HX3V	4HX4V
WATTAGE	600W			600W		
INPUT WATTS	605.7W	604.3W	604.3W	605.5	604.1	604.0
LUMENS	87,867	86,158	85,826	70,685	59,938	65,010
EFFICACY	145.1	142.6	142	116.7	99.2	107.6
CRI	75	76	76	76	77	77
VOLTAGE RATINGS	120-277V			120-277V		

MODEL#	P1M/480			P1M/480 W/GLARE CONTROL SHIELD		
COLOR TEMP	5700K			5700K		
NEMA BEAM SPREAD	2HX2V	3HX3V	4HX4V	2HX2V	3HX3V	4HX4V
WATTAGE	600W			600W		
INPUT WATTS	586.1W	590.4W	590.5W	586.0	590.2	590.2
LUMENS	86,073	84,882	84,769	69,147	59,007	63,889
EFFICACY	146.9	143.8	143.6	118.0	100.0	108.2
CRI	75	76	76	76	77	77
VOLTAGE RATINGS	200-480V			200-480V		

MODEL#	P1L			P1L W/GLARE CONTROL SHIELD		
COLOR TEMP	5700K			5700K		
NEMA BEAM SPREAD	2HX2V	3HX3V	4HX4V	2HX2V	3HX3V	4HX4V
WATTAGE	850W			850W		
INPUT WATTS	843.5W	846.8W	847W	843.4W	846.7W	846.8W
LUMENS	121,128	118,987	113,849	111,364	103,698	79,958
EFFICACY	143.6	140.5	134.4	132	122.5	94.4
CRI	74	76	76	74	76	76
VOLTAGE RATINGS	120-277V			120-277V		

MODEL#	P1L/480			P1L/480 W/GLARE CONTROL SHIELD		
COLOR TEMP	5700K			5700K		
NEMA BEAM SPREAD	2HX2V	3HX3V	4HX4V	2HX2V	3HX3V	4HX4V
WATTAGE	850W			850W		
INPUT WATTS	856.1W	857.4W	857.5W	856.2W	857.4W	857.2W
LUMENS	123,911	121,993	116,570	113,705	105,710	81,840
EFFICACY	144.7	142.3	135.9	132.8	123.3	95.5
CRI	74	76	76	74	76	76
VOLTAGE RATINGS	200-480V			200-480V		

## PERFORMANCE

MODEL	P1XL/480			P1XL/480 W/GLARE CONTROL SHIELD		
COLOR TEMP	5700K			5700K		
NEMA BEAM SPREAD	2HX2V	3HX3V	4HX4V	2HX2V	3HX3V	4HX4V
WATTAGE	1200W			1200W		
INPUT WATTS	1195.3W	1195W	1195.2W	1195.2W	1195.1W	1195.1W
LUMENS	154,568	149,879	146,487	141,434	116,386	105,629
EFFICACY	129.3	125.4	122.6	118.3	97.4	88.4
CRI	76	76	76	76	76	76
VOLTAGE RATINGS	200-480V			200-480V		

## TECHNICAL SPECIFICATIONS

### CONSTRUCTION

#### Cold Weather Starting

Minimum starting temperature is -40°C (-40°F)

#### Maximum Ambient Temperature

Suitable for use in up to 50°C (122°F)

#### Housing

Precision die-cast aluminum

#### Mounting

Standard Yoke Mount. Drivers can be mounted on the fixture bracket on top of the cross arms or remotely on the poles using driver mounting bracket accessories. Slipfitter mount, square beam mount and rail mounting kits sold separately.

#### Tilt Increment

Continuous tilting with 5 degree increments

#### Lens

Polycarbonate

#### Gasket

Silicone

#### Green Technology

Mercury and UV free. RoHs-compliant components.

#### Finish

Formulated for high durability and long lasting color

#### NEMA

NEMA beam spread of 2HX2V, 3HX3V & 4HX4V

#### IP Rating

Ingress protection rating of IP65 for dust and water

#### EPA

MODEL	0°	15°	25°	45°	60°	75°	90°
P1S	1.29	1.29	1.43	1.71	1.87	2.0	2.10
P1M	1.29	1.29	1.43	1.71	1.87	2.0	2.10
P1L	1.67	1.75	1.89	2.25	2.48	2.66	2.77
P1XL	1.67	1.75	1.89	2.25	2.48	2.66	2.77
P1RGB	1.29	1.29	1.43	1.70	1.87	2.0	2.07

## LED CHARACTERISTIC

### LEDS

Long-life, high-efficacy, surface-mount LEDs

### Color Uniformity

RAB's range of Correlated Color Temperature follows the guidelines of the American National Standards for Specifications for the Chromaticity of Solid State Lighting (SLL) Products, ANSI C78.377-2017.

### COMPLIANCE

#### UL Listed

Suitable for wet locations

#### DLC Listed

This product is listed by Design Lights Consortium (DLC) as an ultra-efficient premium product that qualifies for the highest tier of rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.

Model#	Product ID	Model#	Product ID
P1S	S-9DCGGH	P1S/480	S-F7B6ZQ
P1S 2HX2V	S-PL8YHP	P1S/480 2HX2V	S-2FTHKL
P1S 3HX3V	S-T8W5F5	P1S/480 3HX3V	S-OHPWPH
P1M	S-51FM2M	P1M/480	S-ZWXHP5
P1M 2HX2V	S-J1SR7K	P1M/480 2HX2V	S-KWBDB1
P1M 3HX3V	S-K2CRW3	P1M/480 3HX3V	S-H3LFFS
P1L	S-PCL0MK	P1L/480	S-Y6191J
P1L 2HX2V	S-PXGSD9	P1L/480 2HX2V	S-TFMDCP
P1L 3HX3V	S-65507D	P1L/480 3HX3V	S-YGB35J
		P1XL/480	S-X4VKFB
		P1XL/480 2HX2V	S-ZW75C9
		P1XL/480 3HX3V	S-SF1WMX

### ELECTRICAL

#### Drivers:

Constant Current, Class 1, 120-277V, 50/60 Hz

**P1S:** 120V: 4.31A 208V: 2.48A, 240V: 2.15A, 277V: 1.86A

**P1M:** 120V: 5.20A 208V: 3.01A, 240V: 2.61A, 277V: 2.29A

**P1L:** 120V: 6.96A 208V: 4.00A, 240V: 3.45A, 277V: 3.01A

**P1RGB:** 120V: 4.28A 208V: 2.46A, 240V: 2.12A, 277V: 1.84A

#### Drivers:

Constant Current, Class 1, 200-480V, 50/60 Hz

**P1S/480:** 208V: 2.54A 240V: 2.19A, 277V: 1.89A, 480V: 1.09A

**P1M/480:** 208V: 3.01A 240V: 2.61A, 277V: 2.26A, 480V: 1.31A

**P1L/480:** 208V: 4.18A 240V: 3.63A, 277V: 3.15A, 480V: 1.86A

**P1XL/480:** 208V: 6.15A 240V: 5.33A, 277V: 4.61A, 480V: 2.65A

**P1RGB:** 208V: 2.45A 240V: 2.12A, 277V: 1.84A, 480V: 1.05A

#### Dimming Driver:

Driver includes wiring for 0-10V dimming systems. Dim as low as 10%.

**Surge Protection:** 120-277V: 10kV and 200-480V: 20kV

*Note: Lightcloud and Lightcloud Blue models do not require 0-10V dimming circuit.*

# PLAYER ONE SPORTS LIGHT



## TECHNICAL SPECIFICATIONS

### ELECTRICAL

THD/Power Factor:

120-277V MODELS	THD	PF	THD	PF
	120V		277V	
P1RGB @RGB	4.8%	99.6%	4.8%	96.8%
P1RGB @RED	7.1%	98.8%	16.3%	68.1%
P1RGB @GREEN	7.0%	98.2%	20.9%	60.8%
P1RGB @BLUE	6.0%	99.7%	5.7%	93.0%
P1S (2HX2V)	9.1%	99.6%	6.6%	96.5%
P1S (3HX3V)	9.2%	99.6%	6.6%	96.6%
P1S (4HX4V)	9.4%	99.6%	6.7%	96.6%
P1M (2HX2V)	9.6%	99.6%	12.8%	97.3%
P1M (3HX3V)	9.4%	99.6%	12.5%	97.4%
P1M (4HX4V)	9.7%	99.6%	13.1%	97.2%
P1L (2HX2V)	3.6%	99.9%	4.5%	97.7%
P1L (3HX3V)	3.5%	99.9%	4.5%	97.8%
P1L (4HX4V)	3.1%	99.9%	4.7%	97.7%

480V MODELS	THD	PF	THD	PF	THD	PF	THD	PF
	200V		277V		347V		480V	
P1RGB/480 @RGB	6.7%	99.7%	6.0%	99.4%	6.7%	98.9%	10.3%	96.6%
P1RGB/480 @RED	13.3%	97.6%	18.9%	93.9%	21.1%	89.3%	26.4%	89.9%
P1RGB/480 @GREEN	16.0%	96.3%	21.5%	92.5%	24.4%	86.8%	30.5%	72.5%
P1RGB/480 @BLUE	8.3%	99.3%	11.3%	98.0%	13.3%	96.1%	18.0%	67.6%
P1S/480 (2HX2V)	3.8%	99.9%	3.9%	99.9%	4.0%	99.4%	5.3%	95.3%
P1S/480 (3HX3V)	3.6%	99.9%	4.0%	99.9%	4.0%	99.4%	4.5%	95.6%
P1S/480 (4HX4V)	3.5%	99.9%	4.1%	99.9%	3.8%	99.4%	4.4%	95.6%
P1M/480 (2HX2V)	3.8%	99.9%	4.2%	99.9%	4.8%	99.6%	4.9%	97.1%
P1M/480 (3HX3V)	4.0%	99.8%	4.1%	99.9%	5.1%	99.6%	4.5%	97.2%
P1M/480 (4HX4V)	4.0%	99.8%	4.2%	99.9%	5.1%	99.6%	4.9%	97.3%
P1L/480 (2HX2V)	16.6%	98.6%	19.3%	97.7%	20.1%	96.9%	20.5%	94.9%
P1L/480 (3HX3V)	16.8%	98.6%	18.7%	97.8%	19.2%	97.1%	19.7%	95.1%
P1L/480 (4HX4V)	16.7%	98.5%	18.5%	97.8%	19.0%	97.1%	19.7%	95.1%
P1XL/480 (2HX2V)	15.4%	98.8%	17.0%	98.2%	17.8%	97.6%	19.2%	96.3%
P1XL/480 (3HX3V)	15.5%	98.8%	17.2%	98.3%	18.0%	97.7%	19.3%	96.5%
P1XL/480 (4HX4V)	15.4%	98.8%	17.1%	98.3%	17.9%	97.7%	19.4%	96.3%

## TECHNICAL SPECIFICATIONS

### ELECTRICAL

#### THD/Power Factor:

120-277V MODELS	THD	PF	THD	PF
W/GLARE CONTROL SHIELD	120V		277V	
P1S (2HX2V)	9.0%	99.6%	6.6%	96.4%
P1S (3HX3V)	9.2%	99.6%	6.5%	96.7%
P1S (4HX4V)	9.4%	99.6%	6.6%	96.7%
P1M (2HX2V)	9.7%	99.6%	13.0%	97.2%
P1M (3HX3V)	9.3%	99.6%	12.4%	97.5%
P1M (4HX4V)	9.6%	99.6%	13.0%	97.3%
P1L (2HX2V)	3.5%	99.9%	4.7%	97.7%
P1L (3HX3V)	3.2%	99.9%	4.7%	97.8%
P1L (4HX4V)	3.2%	99.9%	4.8%	97.7%

480V MODELS	THD	PF	THD	PF	THD	PF	THD	PF
W/GLARE CONTROL SHIELD	200V		277V		347V		480V	
P1S/480 (2HX2V)	4.0%	99.9%	4.0%	99.9%	4.0%	99.3%	5.3%	95.2%
P1S/480 (3HX3V)	3.3%	99.9%	3.9%	99.9%	4.0%	99.3%	4.4%	95.5%
P1S/480 (4HX4V)	3.4%	99.9%	4.0%	99.9%	4.0%	99.5%	4.6%	95.7%
P1M/480 (2HX2V)	3.9%	99.9%	3.9%	99.9%	4.3%	99.5%	4.9%	97.0%
P1M/480 (3HX3V)	4.0%	99.8%	4.0%	99.9%	5.1%	99.4%	4.5%	97.3%
P1M/480 (4HX4V)	4.0%	99.8%	4.1%	99.9%	5.0%	99.7%	5.0%	97.4%
P1L/480 (2HX2V)	17.3%	98.6%	19.3%	97.7%	20.5%	96.9%	20.5%	94.9%
P1L/480 (3HX3V)	16.9%	98.6%	18.8%	97.8%	19.6%	97.1%	19.5%	95.1%
P1L/480 (4HX4V)	16.6%	98.6%	18.3%	97.8%	19.9%	97.1%	19.7%	95.1%
P1XL/480 (2HX2V)	15.3%	98.8%	17.2%	98.2%	17.9%	97.6%	19.4%	96.3%
P1XL/480 (3HX3V)	14.9%	98.8%	16.9%	98.3%	18.5%	97.7%	19.3%	96.4%
P1XL/480 (4HX4V)	15.3%	98.8%	17.0%	98.3%	18.7%	97.7%	19.3%	96.3%

### RGB MODELS

#### RGB

The RGB option integrates with existing DMX control systems. DMX control system not included with PLAYER ONE models. RGB model will not produce white light.

### OTHER

#### Warranty

The RAB 10-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty)

#### Lifespan

100,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations

## WIRELESS NETWORK LIGHTING CONTROLS


Lightcloud products offer integrated network lighting control for a truly wireless solution that allows you to manage RAB's various compatible devices. With RAB's patented Rapid Provisioning technology, devices can be quickly and easily commissioned for residential and commercial applications. Each device can communicate with other devices in the mesh network. With two Lightcloud systems to choose from, it's easy to implement controls anywhere.

Learn more about Lightcloud wireless networked lighting controls.

Design Lights Consortium Network Lighting Controls:

- Interior Applications: N1XMLOEATB
- Exterior Applications: NHCZ2BIA17L

## Lightcloud®



- Utilizes Bluetooth Mesh, eliminating the need for a Gateway or Hub
- Ideal for applications that need basic wireless control such as ON/OFF, dimming, color tuning, Schedules, and SmartShift
- Download the Lightcloud Blue mobile app for iOS or Android devices
- Add the XDIM/BRIDGE/LCB and LCGATEWAY to adopt premium Lightcloud Enterprise features

### SIMPLE SETUP

- 1** Download the app.
- 2** Connect product
- 3** Pair product to app.
- 4** Enjoy!

Learn more about [Lightcloud Blue](#). Visit the [Lightcloud Blue Resources](#) page for more information on how to use the system.

## Lightcloud®



- Utilizes a secure cellular and Zigbee mesh network that requires a Gateway or Hub (sold separately)
- Offers premium features like remote commissioning, demand response, BACnet integration, and more
- Download the Lightcloud Enterprise mobile app for iOS or Android devices

### SIMPLE SETUP

- 1** Download the app.
- 2** Complete the
- 3** Connect product
- 4** Contact RAB for Remote
- 5** Enjoy!

Learn more about [Lightcloud Enterprise](#). Visit the [Lightcloud Enterprise Resources](#) page for more information on how to use the system.


# PLAYER ONE SPORTS LIGHT



## DIMENSIONS


P1RGB

Weight: 40.08 lbs




P1S/P1M

Weight: 36.55 lbs



P1L/P1XL

Weight: 56.67 lbs



# PLAYER ONE SPORTS LIGHT



## ACCESSORIES

IMAGE	CATALOG#	UPC	DESCRIPTION	WEIGHT
	P1-MR	192552043991	PLAYER ONE POWER BOX MOUNTING RAIL	15.025 lbs
	P1-MR-RGB	192552044004	PLAYER ONE POWER BOX MOUNTING RAIL RGB	16.268 lbs
	P1-SB	192552043984	PLAYER ONE SQUARE BEAM MOUNTING KIT BLACK	12.302 lbs
	P1-SF	192552043977	PLAYER ONE SLIPFITTER ADAPTOR BLACK	4.079 lbs
	P1-13C	192552044011	PLAYER ONE EXTENSION CORD 164FT 18AWG 600V BLACK	13.596 lbs
	P1GCS-S-M	192552044035	PLAYER ONE UP TO 600W GLARE CONTROL SHIELD BLACK	0.49 lb
	P1GCS-L-XL	192552044028	PLAYER ONE 850W AND UP GLARE CONTROL SHIELD BLACK	1.695 lbs
	P1-LAS	192552044042	PLAYER ONE LASER AIMING SIGHT 3.7V 532NM GREEN LIGHT	0.143 lb

## ORDERING MATRIX

### P1-PLAYER ONE

Family	Size/ Wattage	Color Temperature	Mounting	Optics	Finish	Driver	Control
P1							
S	Small / 500W	BLANK 5700K	BLANK Yoke Mount	BLANK 4HX4V	BLANK Black	BLANK 120-277V	BLANK No Option
M	Medium / 600W			B33 3HX3V		0-10V Dimming	/LC Lightcloud
L	Large / 850W			B22 2HX2V		/480 200-480V	/LCB Lightcloud Blue
XL	Extra Large / 1200W *					0-10V Dimming	

Family	Wattage	Color Temperature	Mounting	Optics	Finish	Driver
P1		RGB				
	BLANK 480W	RGB	BLANK Yoke Mount	BLANK 4HX4V	BLANK Black	BLANK 120-277V DMX
						/480 200-480V DMX

\*XL only available in 200-480V models