

RAB®

TRACK PENDANT



The ultra-slim Track Pendant.

A contemporary lighting solution for all your spaces.

Flexibility in a sleek package.

Designed for 120V use, the small Track Pendant delivers focused, single-CCT performance while the medium model boasts three field-adjustable color temperatures, so you can fine-tune your lighting on-site without managing multiple SKUs.





FEATURE PAGE



5-YEAR LIMITED WARRANTY

RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty



Versatile, superior-quality output.

The 36° beam angle is ideal for adding ambience to homes or providing balanced illumination in stores and hospitality. With 90+ color rendering, the Track Pendant ensures that your colors appear vibrant and true to life in any application.



Effortless installation and versatility.

Simple track mounting makes positioning and repositioning a breeze, perfect for retail, hospitality, or residential applications. Available in both black and white finishes to complement any design aesthetic.



Complete design solutions.

Track Pendant is fully compatible with our track system components, which include various track lengths, joiner configurations, and power feeds.

- 2 ft H-Track
- 4 ft H-Track
- 6 ft H-Track
- 8 ft H-Track
- Conduit Feed
- Top Access End Feed
- T-Bar End Feed
- 12 ft Grounded Cord+Plug
- I-Joiner
- X-Joiner
- L-Joiner
- T-Joiner
- Flexible Connector
- Track End Cap
- Floating Canopy Feed
- Junction Box End Feed
- Monopoint Luminaire Adaptor
- Duopoint Luminaire Adaptor
- Pendant Luminaire Adaptor
- Suspension Mount Canopy Kit
- Suspension Sloped Ceiling Kit
- Suspension Wire Cable Kit
- 6" Track Suspension Stem
- 12" Track Suspension Stem
- 24" Track Suspension Stem
- 36" Track Suspension Stem
- Track Suspension Stem Coupler
- Track Monopoint Sloped Ceiling Adaptor
- Suspension Top Access End Feed Wire Cover
- Junction Cover Plate

Ordering Matrix

Product Family	Size/Wattage	Mount	Color Temp	Optics	Finish	Driver
TKP	S Small/8W M Medium/8W	Blank H-Track Mount	Blank Y 3000/4000/5000K* 3000K	Blank 36° Beam Angle	Blank B White Black	Blank 120V, TRIAC Dimming

*Selectable CCT available only with Medium.